

EcoTUFF, similar to InterpreTUFF, offers the same high quality, full color image on a rigid, yet lightweight polymetal board perfect for a variety of uses. The polymetal used for EcoTUFF has a thinner aluminum facing, but the same overall thickness as InterpreTUFF, allowing us to offer the same great quality printed sign for a fraction of the cost. These signs can be framed for added protection or manufactured with predrilled holes for easy mounting on wooden posts.

DISPLAY OPTIONS

Exhibit Base/Frame

We encourage the use of a frame system for displaying EcoTUFF signs. This helps provide additional protection and support for the sign.

We offer heavy gauge, powder coated aluminum frame system with a variety of options to fit the needs of your signs and budget.

Unframed Signs

For smaller EcoTUFF signs, or signs not being framed, we offer additional finishing options, such as predrilled holes and rounded corners.

Finishing Option Standards Measurements:

Holes:

- 3/16 inch diameter
- 1 inch in from sign edge
- Located in each corner or centered on the top and bottom of sign

Rounded Corners:

- 3/8 inch radius

TECHNICAL SPECIFICATIONS

- Digital print on 3.8 mil vinyl with 2 mil permanent adhesive
- Protected by 8 mil velvet texture laminate
 - UV-blocking to keep your graphics clear and bright for up to 9 years
 - Chemical resistant protects from harsh conditions, including bleach, cleaners, acid and more
 - Scratch and abrasion resistant protects against the elements to keep graphics readable
- Withstands a wide range of temperatures (-40°F to 175°F)
- Applied to 3mm polymetal board
 - 0.15 mm aluminum facing with a polyethylene core
- Assembled sign thickness: 0.135 inch
- Fits nicely in most frame systems made to accommodate 1/8 inch sign panels
- Expected lifespan of 3-7+ years